

SPECIFICATIONS

Amplifier Section

Power Output

Front L/R	140 W/Ch (6 Ω , 1 kHz, 1 channel driven, IEC)
Center	140 W (6 Ω , 1 kHz, 1 channel driven, IEC)
Surround L/R	140 W/Ch (6 Ω , 1 kHz, 1 channel driven, IEC)
Surround Back L/R	140 W/Ch (6 Ω , 1 kHz, 1 channel driven, IEC)

Dynamic Power	210 W (3 Ω , 1 ch)
	180 W (4 Ω , 1 ch)
	110 W (8 Ω , 1 ch)

THD (Total Harmonic Distortion)	0.08% (1 kHz, 1W Output)
--	--------------------------

Damping Factor	60 (Front, 1 kHz, 8 Ω)
-----------------------	--------------------------------

Input Sensitivity and Impedance	200 mV/47 k Ω (Line)
--	-----------------------------

Output Level and Impedance	200 mV/2.2 k Ω (Rec out)
-----------------------------------	---------------------------------

Frequency Response	5 Hz–100 kHz/+1 dB, -3 dB
---------------------------	---------------------------

Tone Control	\pm 10 dB, 50 Hz (Bass)
	\pm 10 dB, 20 kHz (Treble)

Signal-to-Noise Ratio	106 dB (Line, IHF-A)
------------------------------	----------------------

Speaker Impedance	4 Ω –16 Ω or 6 Ω –16 Ω
--------------------------	--

Video Section

Input Sensitivity/Output Level and Impedance

Video	1.0 V _{p-p} /75 Ω (Component)
	0.7 V _{p-p} /75 Ω (Component P _B /C _B , P _R /C _R)
	1.0 V _{p-p} /75 Ω (Composite)

Component Video Frequency Response	5 Hz–50 MHz, -3 dB
---	--------------------

Tuner Section

Tuning Frequency Range

FM	87.5 MHz–108 MHz
AM	522 kHz–1,611 kHz

FM/AM Preset Memory	40 stations
----------------------------	-------------

General

Power Supply	AC 230 V~, 50 Hz
---------------------	------------------

Power Consumption	550 W
--------------------------	-------

Dimensions (W x H x D)	435 x 176 x 329 mm
-------------------------------	--------------------

Weight	11.0 kg
---------------	---------

■ CARTON

Dimensions (W x H x D)	570 x 297 x 423 mm
-------------------------------	--------------------

Weight	14.7 kg
---------------	---------